



Camara UniFi G5 Pro — 4K 8MP

Zoom Optico 3x IR 25m IP65 PoE

UBT-UVC-G5-PRO



Hardware

| | |
|--------------------------|---|
| Dimensiones | Ø86 x 154.3 mm |
| Peso | 650 g |
| Material | Policarbonato UV + aleacion de aluminio |
| Alimentacion | PoE — 37-57V DC, max 10W |
| Puerto red | 10/100 MbE RJ45 |
| Temperatura de operacion | -20°C a 50°C |
| Proteccion climatica | IP65 |
| Resistencia a golpes | IK04 |
| Cumplimiento NDAA | Si |
| Certificaciones | CE, FCC, IC |

Video e imagen

| | |
|-------------------|--------------------------------|
| Resolucion | 8MP 3840 x 2160 (16:9) — 4K |
| Sensor | 1/2" 8MP |
| Frame rate maximo | 30 FPS |
| Zoom | Optico 3x (F 4.1-12.3 mm) |
| FoV amplio | H: 109.9° / V: 60° / D: 127.7° |
| FoV tele (3x) | H: 35° / V: 19.8° / D: 40° |

| | |
|-----------------|--|
| Vision nocturna | IR 25 m (hasta 40 m con Vision Enhancer) |
| Detecciones IA | Personas, vehiculos, animales |
| Audio | Microfono integrado |

Montaje

| | |
|----------|--|
| Incluido | Pared, techo, poste (diametro 38-50mm) |
| Opcional | Junction box, base angulada, Vision Enhancer (LED IR + floodlight) |